# Schleuniger



Innovators in Wire Processing

CoaxStrip 5300
Coaxial Cable Stripping Machine



# echnical Specifications subject to change ◎ Schleuniger Group, 3608 Thun, Switzerland / CS\_5300\_DS\_EN\_A4\_V6

# Schleuniger

## CoaxStrip 5300

### Concept

The CoaxStrip 5300 is a fully programmable multi-step stripping machine for coaxial, triaxial, multi-conductor cable and single conductor wire. State-of-the-art electronics, a user-friendly graphic display and precision mechanics guarantee repetitive, unmatched Schleuniger stripping quality. With a sample programming library and 1000 program memory , this machine is ideal for low volume, quick changeover applications as well as high volume production runs, giving the best possible flexibility and productivity to your production methods.

### Programmable settings for each step of each program:

- Stripping position
- Stripping diameter
- Feed rate of the stripping blades
- Rotational speed of the stripping head
- Spindle direction of the stripping head
- Extra spin time of the stripping head
- Wayback (opens blades slightly before pulling off)
- Stripping lengths (partial strip or full strip)
- Pull-off speed
- Pull-off with or without rotation of the stripping head
- Freely selectable stripping sequence
- Cable clamping force

### **Special features**

- Wire list processing
- Iguana <sup>™</sup> Wire Processing software (optional)
- Diagnostics features
- Password protect with different user levels

# Technical Specifications

Max. Cable Diameter	7 mm (0.276")
Diameter Increments	0.01 mm (0.01")
Max. Stripping Length	30 mm (1.18")
Stripping Length Increments	0.01 mm (0.01")
Max. Stripping Steps	9
Cable Clamping	Motor driven with programmable clamping force
Cycle Time	≥ 4 s (depending upon cable type and programming)
Production Rate	300 - 650 pcs./h (depending upon cable type and programming)
Program Capacity	1000 cables / 100 wire lists
Interfaces	RS 232, foot pedal, robotic interface (option)
Noise Level	< 70 db (A)
Power Supply	100/115 VAC: fuse 2.0 A/T, 230/240 VAC: fuse 1.0 AT, 50/60 Hz, 100 VA
Dimensions (L x W x H)	494 x 140 x 218 mm (19.4 x 5.5 x 8.6")
Weight	9.7 kg (21 lbs.)
CE–Conformity	The CoaxStrip 5300 complies fully with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.
Important Note	Schleuniger recommends that wire samples be submitted in cases where there is doubt as to the processing capabilities of a particular machine.

Sales and Service by:

Schleuniger Group Thun | Switzerland www.schleuniger.com